

PNEUMATICKÉ PROTLAKY

HAMMERHEAD

AH = AKTIVNÍ HLAVA | RH = PASIVNÍ HLAVA | CAT = CATAMOUNT
 PP = POWER PORT | SR = SCREW REVERSE | SW = SIDEWALKER | MT = MOLETRAC

TYP PROTLAKU	PRŮMĚR	DÉLKA	HMOTNOST	SPOTŘEBA VZDUCHU
2" AH PP SW	50 MM	77 cm	8 kg	425 l/min
2" RH SR	50 MM	115 cm	13 kg	623 l/min
2" RH PP	50 MM	99 cm	11 kg	510 l/min
2.5" CAT	67 MM	125 cm	23 kg	878 l/min
2.5" RH SR / MT	67 MM	123 cm	23 kg	878 l/min
2.5" RH PP / MT	67 MM	123 cm	23 kg	878 l/min
2.5" AH PP	67 MM	127 cm	23 kg	878 l/min
2.5" RH SR SW / MT	67 MM	85 cm	15 kg	991 l/min
3" CAT	75 MM	129 cm	31 kg	906 l/min
3" RH SR / MT	75 MM	133 cm	30 kg	991 l/min
3" RH PP / MT	75 MM	131 cm	30 kg	991 l/min
3" AH PP	75 MM	133 cm	30 kg	991 l/min
3" RH PP SW / MT	75 MM	106 cm	23 kg	934 l/min
3.5" CAT	89 MM	150 cm	45 kg	1515 l/min
3.5" RH PP / MT	89 MM	150 cm	43 kg	1515 l/min
4" CAT	100 MM	167 cm	67 kg	1840 l/min
4" RH PP / MT	98 MM	160 cm	59 kg	1812 l/min
4" RH SR / MT	98 MM	162 cm	62 kg	1926 l/min
4.375" CAT	111 MM	159 cm	82 kg	2549 l/min
5.125" CAT	130 MM	182 cm	117 kg	4539 l/min
5.125" RH SR	130 MM	167 cm	97 kg	2775 l/min
5.125" RH PP	130 MM	165 cm	111 kg	4531 l/min
5.5" RH SR BU	140 MM	162 cm	77 kg	1926 l/min
5.625" RH PP BU	143 MM	165 cm	113 kg	4531 l/min
5.75" RH SR	145 MM	202 cm	138 kg	3738 l/min

HAMMERHEAD®